



Standard Specifications

BASIC CONSTRUCTION

- Patented Air-Flow contoured shape
- Exclusive Aero-Stress® high-strength steel undercarriage
- Extrusion-formed aluminum bumper bolted to undercarriage
- Exclusive super Dura Torque® rubber torsion bar axles
- Shock absorbers on all wheels
- Tandem wheels on models 25' and longer
- 12 volt electric brakes on all wheels – can be coordinated with foot brake pedal in car
- 7:00 x 15 Truck-type extra strength wheels with nylon tubeless tires (6 ply on 18 foot Caravel and 21 foot Globetrotter; 8 ply on 23 foot Safari; 6 ply on all tandem axle models)
- Hand riveted double-shell body of heat treated structural alloy aluminum
- Ribs of stretch-formed structural alloy aluminum
- Interior walls of wear-resistant vinyl laminated to aluminum
- One-piece aluminum window frames riveted to body

- Exterior protective acrylic coating
- Exclusive contoured Jet-Seal awning-type safety glass windows
- Corrosion-proof screens in all windows
- Front window guard of transparent Butyrate
- Insulated, unitized door and screen door
- Exclusive touch-control fold-away steel step, welded to frame
- Trunk compartment with lock and insulated door
- * Rear service area for storage of water line, 110 volt power cord, 12 volt battery and septic tank valve
- Univolt convenience light in rear service area and trunk
- Awning rail
- Seamless, dustproof, one-piece polyethylene wheel housings
- Adjustable, no-draft aluminum roof vents
- 2½ inch aircraft type fibreglass insulation
- Automatic electric break-away switch
- Exterior clearance and running lights and reflectors installed in conformance with Federal Motor Vehicle Safety Standards
- Back-up lights
- Weather-proof exterior 110 volt outlet
- Built-in 110 volt service line (25 feet)
- Extra-capacity 90 ampere hour 12 volt battery in vented case
- Battery charger with protective voltage regulator
- Univolt ceiling exhaust fan in bathroom
- Three-position Univolt interior lights (operate on 110 volt or 12 volt current)
- Interior 110 volt convenience outlets
- Automatically resetting circuit breaker on Univolt
- Overload safety fuse cartridges on Univolt wiring system
- Circuit breakers on 110 volt wiring system

ELECTRICAL EQUIPMENT

- U.S.A.S.I. and D.O.H. Code-approved wiring system
- Detachable single-plug weatherproof car-trailer connector (includes 12 volt charge line)
- Two-bulb, corrosion-proof 180° visibility exterior clearance and running lights

PLUMBING

- U.S.A.S.I. and D.O.H. Code-approved plumbing system
- High volume water pressure regulator in water inlet line
- Univolt marine water pump (capacity 3 gallons per minute)
- 50 Gallon polyethylene water tank
- † Swing faucet at galley sinks

