

STANDARD SPECIFICATIONS

CONSTRUCTION

• Sealed Air-Flow contoured shape.
• Gas electro-welded high-strength steel carriage.
• Torque rubber torsion bar axles.
• Shock absorbers on all wheels.
• 15 wheels on 22', 24', 26' and 28'.
• 15 wheels on 20'.
• Electric brakes on all wheels—can be operated with foot brake pedal in car.
• Lock type extra strength wheels with 15 nylon tubeless tires (8 ply on single models; 6 ply on tandem axle models).
• Riveted monocoque shell.
• Rust protection: Automotive type alkyd enamel.
• 100% of stretch-formed structural alloy aluminum.
• Interior walls of wear-resistant vinyl laminated to aluminum.
• 100% piece stretch-formed extruded aluminum window frames riveted to body.
• Exclusive contoured Jet-Seal awning-type ultralite safety glass windows.
• Laminated acrylic front windows using super strength ultralite safety glass.
• Insect proof screens in all windows.
• Exclusive touch control fold away steel insect step.
• Running rail.
• Double walled fiberglass insulated wheel wells.
• Aircraft type fiberglass insulation.
• Stable no draft aluminum roof vents.
• Tire hub caps.
• Easy to close and lock water fill.

CENTRAL EQUIPMENT

• A.N.S.I., D.O.H. and C.S.A. code approved lighting system.
• Single plug weatherproof car trailer connector includes 12 volt charge line).
• 12 volt bulb, corrosion proof 180° visibility front clearance and running lights installed in conformance with Federal Motor Vehicle Safety Standard 108).
• Automatic electric break-away switch.

- Back up lights.
- Built in 110 volt service line (25 feet).
- Extra capacity 72 ampere hour 12 volt battery in built in sealed and vented battery compartment.
- Three position Univolt 4 bulb ceiling lights.
- One knob variable position ceiling vents.
- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery.
- Automatic resetting circuit breaker.
- Overload safety fuse cartridges in Univolt wiring system.
- High intensity adjustable reading lights.
- Circuit breakers on 110 volt wiring system.
- Polarity warning light.

PLUMBING

- A.N.S.I., D.O.H. and C.S.A. code approved plumbing system.
- High volume water pressure regulator in water inlet line.
- Univolt marine water pump (capacity 3 gallons per minute).
- 30 gallon polyethylene water tank.
- Swing faucet at galley sinks.
- Porcelain galley sinks. (Color coordinated.)
- Exclusive all thermo formed bathroom with bathtub in 26', 28', shower room in 20', 22' and 24'.
- Built in medicine chest and mirror.
- Telephone shower head.
- Marine type toilet.
- Polyethylene holding tank.
- Drainage drop out cover cap.
- Drainage drop out elbow for connecting sewer hose.
- Built in sewer hose carrier.
- Accessible dump valve.

GAS EQUIPMENT

- A.N.S.I., D.O.H. and C.S.A. code approved gas system.
- All gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers.

- Double five gallon gas bottles with rack.
- Sealed outside vented heater (input ratings: 20', 22' = 16,000 BTU; 24', 26', 28' = 22,000 BTU).
- Automatic heater thermostat.
- Univolt sealed combustion system with dual blower and forced circulating ducts.
- Gas/electric combination refrigerator: 4.5 cubic foot in 20' and 22'. 6.0 cubic foot in 24', 26' and 28'.
- Gas range with oven and broiler.
- Range vent hood.
- 6 gallon gas water heater.

FURNISHINGS

- Exclusive perma-tech furniture construction featuring heat treated anodized aluminum framework with textured laminate panels.
- Lightweight warp free hollowcore doors.
- Roll away doors in front roof locker.
- Travel sure locks on all cabinet doors.
- Lightweight injection molded drawers.
- Credenza fold away table in all models with front travel lounge.
- 5 inch foam mattresses in bedroom with zippered covers.
- Nylon shag carpet in all areas.
- All upholstery treated with SCOTCHGARD repeller to resist soiling.
- All draperies fade resistant and self lined.
- Decorator styled washable vinyl window shades at galley and bathroom windows.
- Slide away bathroom door.
- Bedroom vinyl folding door (24', 26' and 28' only).
- Choice of four color schemes.

DIMENSIONS:

- Outside floor width . . . 7' 8".
- Outside height from ground . . . 8' 10".
- Inside height (floor to ceiling) . . . 6' 7".
- Ground clearance . . . 16" to underbelly. 12.24" to axle tube.
- Recommended hitch ball height . . . 19½".
- All specifications subject to change without notice.