

STANDARD SPECIFICATIONS

CONSTRUCTION

Aerodynamic Air-Flow contoured shape.
Gas electro-welded high-strength steel carriage.
Torque rubber torsion bar axles.
Shock absorbers on all wheels.
Stainless steel wheels on 22', 24', 26', and 28'.
Electric brakes on all wheels — can be activated with foot brake pedal in car.
Duck type extra strength wheels with 7:00 x 15 tubeless tires (D-rated on single axle models; E-rated on double axle models).
Riveted monocoque shell.
Corrosion protection: Automotive type alkyd enamel.
Extruded stretch-formed structural alloy aluminum.
Interior walls of wear-resistant vinyl laminated aluminum.
Extruded piece stretch-formed extruded aluminum window frames riveted to body.
Five contoured Jet-Seal awning-type Herculite glass windows.
Aluminum laminated front windows using super strength safety glass.
Insect repellent screens in all windows.
Interior touch control fold away aluminum step.
Interior hand rail.
Fiberglass insulated wheel wells.
Aircraft type fiberglass insulation.
Draft stop aluminum roof vents.
Stainless steel wheels.

OPTIONAL EQUIPMENT

12 volt battery, D.O.H., C.S.A. and N.E.C. code approved charging system.
Plug weatherproof car trailer connector (includes 12 volt charge line).
Light bulb, corrosion proof 180° visibility exterior clearance and running lights (installed in accordance with Federal Motor Vehicle Safety Standard 108).
Automatic electric break-away switch.
Interior map lights.

- Built in 110 volt service line (25 feet).
- Extra capacity 72 amperes hour 12 volt battery; built in sealed and vented battery compartment.
- Three position Univolt 4 bulb ceiling lights.
- One knob variable position ceiling vents.
- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery.
- Overload safety fuse cartridges in Univolt wiring system.
- High intensity adjustable reading lights.
- Circuit breakers on 110 volt wiring system.
- Polarity warning light.

PLUMBING

- A.N.S.I., D.O.H. and C.S.A. code approved plumbing system.
- High volume water pressure regulator in water inlet line.
- Univolt water pump.
- 30 gallon polyethylene water tank.
- Swing faucet at galley sinks.
- Stainless steel galley sinks.
- Exclusive all thermo formed bathroom with bathtub in rear bath 26', 28', shower room in 22', 24' and 28' center bath.
- Built in medicine chest and mirror.
- Telephone shower head.
- Mechanical seal toilet.
- Polyethylene holding tanks.
- Drainage drop out cover cap.
- Drainage drop out elbow for connecting sewer hose.
- Built in sewer hose carrier.
- Accessible dump valve.
- Lockable, flush water fill.

GAS EQUIPMENT

- A.N.S.I., D.O.H. and C.S.A. code approved gas system.
- All gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers.
- Double five gallon gas bottles with rack.

- Sealed outside vented heater (input ratings: 22' = 16,000 BTU; 24', 26', 28' = 22,000 BTU).
- Automatic heater thermostat.
- Univolt sealed combustion system with forced air circulating ducts.
- Gas/electric combination refrigerator: 4.5 cubic foot in 22'. 6.0 cubic foot in 24', 26' and 28'.
- Gas range with oven and broiler.
- Range vent hood.
- 6 gallon gas water heater.

FURNISHINGS

- Exclusive Perma-Tech furniture construction featuring heat treated anodized aluminum framework with textured vinyl panels.
- Lightweight warp free hollowcore doors.
- Tambour doors in all roof lockers.
- Tambour cabinet doors.
- Posi-Lok latches on all cabinet doors.
- Lightweight injection molded drawers.
- Credenza table in all models with front travel lounge.
- Bedroom wall comfort covers.
- Foam mattresses in bedroom with zippered covers.
- Nylon shag carpet in all areas.
- All upholstery treated with SCOTCHGARD repeller to resist soiling.
- All draperies fade resistant.
- Decorator styled washable vinyl window shades at galley and bathroom windows.
- Lined drapes.
- Slide away bathroom door.
- Bedroom vinyl folding door. (24', 26' and 28' only).
- Choice of three color schemes.
- Fire extinguisher.

DIMENSIONS

- Outside floor width . . . 7'8".
- Outside height from ground . . . 8'10".
- Inside height (floor to ceiling) . . . 6'7".
- Ground clearance . . . 16" to underbelly. 12.24" to axle tube.
- Recommended hitch ball height . . . 19½".
- All specifications subject to change without notice.